

HID

High Bay

UL Type B



50K-Hour Lifespan		Catalog Number	Wattage	Lumens ¹	Efficacy ¹	Base	Input Voltage	Case Qty.	Color Temp.
High Bay	400W ²	HID-115-V-EX39-8xx-BYP-HB-G2	115	15800	137	EX39	100-277	4	
	250W ²	HID-80-V-EX39-8xx-BYP-HB-G2	80	10800	135	EX39	100-277	4	
	200W ²	HID-60-V-EX39-8xx-BYP-HB-G2	60	8100	135	EX39	100-277	4	


XX in catalog numbers signifies several color temperatures available.

40 = 4000K 50 = 5000K



1. Numbers are nominal 2. Equivalent wattage


ACCESSORIES	Catalog Number	Description	Case Qty.
	SP10KV	10kV surge protector	30
	XFMR200-480-277	Step down transformer	8



Features

- Replacement for traditional Metal Halide or High Pressure Sodium HID lamps
- Produces 10% uplight
- Integral driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Rated for use in enclosed and open fixtures in dry or damp locations
- 4kV surge protection built in
- Environmentally friendly, no mercury used
- UL Listed, UL Classified, DLC Listed
- Non-dimmable
- 5-Year, no-compromise warranty
- Lamp includes on board low-voltage AUX port for lamp level sensor accessories

Dimensions



	A	B	C
400W	9 1/8"	2 3/8"	9 1/8"
250W	7 7/8"	2 3/8"	6 7/8"
200W	6 7/8"	2"	6 3/8"

Measurements in inches