


BASE IDENTIFICATION




Medium Base



Candelabra




Mogul




GU5.3



GU10



G13



Medium Adaptor

HOW TO READ PRODUCT INFORMATION – LED

Nominal Wattage	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Beam Angle (deg)	Average Rated Life (hrs)	CCT (K) CRI	Approx. Initial Lumens at 25°C/77°F	Life in Years	Cost per Year	Notes
-----------------	----------	------	----------------	-----------------------	---------	------------------	--------------------------	-------------	-------------------------------------	---------------	---------------	-------

Base See Base Identification above.

Notes All notes that apply to a specific product will appear in this space. The explanations of the notes are in the notes section.

Ordering Abbreviation A text description of the lamp. See below for several examples and explanations of some of the codes.

Lumens, Beam Angle, CBCP These columns may contain data for any of these values.

HOW TO READ ORDERING ABBREVIATIONS

LED12A19/DIM/0/827		LED13PAR30LN/DIM/827/FL40		LED/RT6/700/827/FL80		LED12T8/L48/FG/830/SUB/G6	
LED	Lamp technology	LED	Lamp technology	LED	Lamp technology	LED	Lamp technology
12	Nominal wattage	13	Nominal wattage	RT6	Retrofit 6" housing	12	Nominal wattage
A19	Lamp shape	PAR30LN	Lamp shape	700	Lumen output	T8	Lamp shape
DIM	Dimmable	DIM	Dimmable	827	CRI: 80+; Color temperature 2700K	L48	Length: 48 inches
0	Omnidirectional	827	CRI: 80+; Color temperature 2700K	FL80	Flood 80°	FG	Frosted Glass
827	CRI: 80+; Color temperature 2700K	FL40	Flood 40°			830	CRI: 80+; Color temperature 3000K
						SUB	SubstiTUBE
						G6	6th Generation LED Lamp technology

¹Life in years based on 3 hours per day

²Cost per year based on 3 hours per day, \$0.11 per kWh